



TRD1600-8000L VACUUM TRUCK

HYDRO EXCAVATION TRUCK

CALL 1800 618 963 | Visit <https://vorstrom.com.au>

NSW Office: Level 6, 10 Herb Elliott Ave Sydney Olympic Park NSW 2127

QLD Office: 14 Project St, Warwick QLD 4370



Engineered for HIGH PERFORMANCE

KEY FEATURES

- 8000L spoil Capacity
- Tipping tank with double acting ram
- Manufactured in Australia in accordance with ASI554.1 GP
- 1800mm x 8mm Barrel and 8mm Tori spherical ends
- 1600CFM Blower 5314 vacuum pump vacuum and pressure mode
- Pressure/Vacuum Gauge
- 150mm Primary shut off & 150mm secondary shutoff
- 1 x Pressure relief valve & Vacuum Relief Valve
- 100mm top load Brass inlet valve with removable wear plate & 150mm rear Brass discharge valve fitted with caps
- 100mm dewatering system with valve and caps
- Full Opening Rear door with 4 x over centre locking clamps and spoil scoop
- Hydraulic system to operate the Pump, rear door, tipping ram, Suction boom.
- 2 x emergency stop to shut down vacuum system only
- 1 x Pressure Cleaner, triplex brass head pump engine driven.
- High Pressure hose with Hose Reel and hand Gun & Lance
- Suction Boom: 4"(100mm) Manifold diameter
- Remote grease lines to be fitted to the suction boom and rear door pivot system
- Hydraulically operated
- Air operated Shutter valve
- Remote Radio Push button control panel (with emergency stop button)
- Extendable by 1350mm with a total reach of 5 meters
- Maximum Rotation Angle of 300Deg
- 3000L water capacity mounted in front mounted water tank
- Roll over protection
- Bunded Aluminium hose trays

For more information about this unit,
please call 1800 618 963.